



For L/D=5

Dia. øD _c	Cat. No.	Stock	Dimensions (mm)					Applicable inserts	Max. offset	Clamping screw	Torx wrench	Hex. wrench	Plug screw								
			øD _s	øD ₂	ℓ	ℓ _s	L														
12.5	TDX125L063W20-5	●	20	32	62.5	43	128	XPMT040104R-DJ XPMT040104R-DS XPMT040104R-DW	0.8	CSTB-2	T-6D										
13.0	TDX130L065W20-5	●			65.0		131		0.7												
13.5	TDX135L068W20-5	●			67.5		134		0.5												
14.0	TDX140L070W20-5	●			70.0		137		0.4												
14.5	TDX145L073W20-5	●			72.5		140		0.3												
15.0	TDX150L075W20-5	●			75.0		143		0.9												
15.5	TDX155L078W20-5	●			77.5		146		0.8												
16.0	TDX160L080W20-5	●			80.0		148		0.6												
16.5	TDX165L083W20-5	●			82.5		152		0.5												
17.0	TDX170L085W20-5	●			85.0		154		0.4												
17.5	TDX175L088W25-5	●			25		37		87.5					50	XPMT06X308R-DJ XPMT06X308R-DS XPMT06X308R-DW	1.2	CSTB-2.2R	T-7D			
18.0	TDX180L090W25-5	●							90.0							168					1.1
18.5	TDX185L093W25-5	●							92.5							171					0.9
19.0	TDX190L095W25-5	●							95.0							173					0.8
19.5	TDX195L098W25-5	●	97.5	176		0.7															
20.0	TDX200L100W25-5	●	100.0	180		0.5															
20.5	TDX205L103W25-5	●	102.5	182		0.4															
21.0	TDX210L105W25-5	●	105.0	185		0.3															
21.5	TDX215L108W25-5	●	107.5	188		0.2															
22.0	TDX220L110W25-5	●	110.0	191		1.2															
22.5	TDX225L113W25-5	●	112.5	193		1.1															
23.0	TDX230L115W25-5	●	115.0	196		0.9															
23.5	TDX235L118W25-5	●	117.5	199		0.8															
24.0	TDX240L120W25-5	●	120.0	202		0.7															
24.5	TDX245L123W25-5	●	122.5	205	0.5																
25.0	TDX250L125W25-5	●	125.0	208	0.4																
25.5	TDX255L128W25-5	●	127.5	211	0.3																
26.0	TDX260L130W25-5	●	130.0	213	0.2																
27.0	TDX270L135W32-5	●	32	40	135.0	55	XPMT07H308R-DJ XPMT07H308R-DS XPMT07H308R-DW	1.5	CSTB-2.5	T-8D											
28.0	TDX280L140W32-5	●			140.0			225					1.2								
29.0	TDX290L145W32-5	●			145.0			231					1.0								
30.0	TDX300L150W32-5	●			150.0			237					0.7								
31.0	TDX310L155W32-5	●			155.0			243					0.4								
32.0	TDX320L160W32-5	●			160.0			248					0.2								
33.0	TDX330L165W40-5	●			40			50					165.0	65	XPMT08T308R-DJ XPMT08T308R-DS XPMT08T308R-DW	2.3	CSTB-3	T-9D			
34.0	TDX340L170W40-5	●											170.0			254					2.1
35.0	TDX350L175W40-5	●											175.0			254					1.8
36.0	TDX360L180W40-5	●											180.0			254					1.5
37.0	TDX370L185W40-5	●											185.0			254					1.3
38.0	TDX380L190W40-5	●											190.0			254					1.0
39.0	TDX390L195W40-5	●											195.0			254					0.7
40.0	TDX400L200W40-5	●											200.0			254					0.5
41.0	TDX410L205W40-5	●	205.0	254		0.2															
42.0	TDX420L210W40-5	●	55	55		210.0	65		XPMT110412R-DJ XPMT110412R-DS XPMT110412R-DW	3.1	CSTB-3	T-15D									
43.0	TDX430L215W40-5	●				215.0				324											2.9
44.0	TDX440L220W40-5	●				220.0				330											2.6
45.0	TDX450L225W40-5	●				225.0				336											2.3
46.0	TDX460L230W40-5	●				230.0				341											2.1
47.0	TDX470L235W40-5	●			235.0	348		1.8													
48.0	TDX480L240W40-5	●			240.0	353		1.5													
49.0	TDX490L245W40-5	●			245.0	359		1.3													
50.0	TDX500L250W40-5	●			250.0	365		1.0													
51.0	TDX510L255W40-5	●			255.0	370		0.7													
52.0	TDX520L260W40-5	●			260.0	376		0.5													
53.0	TDX530L265W40-5	●			265.0	382		—													
54.0	TDX540L270W40-5	●			270.0	388		—													

Note: L/D=Hole depth/Drill diameter

● : Stocked in Japan.